

<b>Requested document:</b>	<a href="#">EP1095951 click here to view the pdf document</a>
----------------------------	---

## PROPYLENE POLYMER AND COMPOSITION CONTAINING THE SAME, MOLDED OBJECT AND LAMINATE COMPRISING THESE, AND PROCESSES FOR PRODUCING PROPYLENE POLYMER AND COMPOSITION CONTAINING THE SAME

Patent Number: EP1095951  
Publication date: 2001-05-02  
Inventor(s): KASHIWAMURA TAKASHI (JP); KAKIGAMI KOJI (JP); KIJIMA MASATO (JP); MINAMI YUTAKA (JP); MOGI YASUHIRO (JP); TANI NORIYUKI (JP); FUNABASHI HIDEO (JP); KANAMARU MASAMI (JP); OKAMOTO TAKUJI (JP); OTA TSUYOSHI (JP); SETA YASUSHI (JP)  
Applicant(s): IDEMITSU PETROCHEMICAL CO (JP)  
Requested Patent:  [EP1095951](#)  
Application Number: EP19990926823 19990625  
Priority Number(s): WO1999JP03405 19990625; JP19980179252 19980625; JP19980210115 19980724; JP19980239872 19980826; JP19980302892 19981023; JP19990000283 19990105; JP19990055025 19990303; JP19990079694 19990324; JP19990086491 19990329; JP19990093420 19990331; JP19990103996 19990412  
IPC Classification: C08F10/06; C08F4/642; C08L23/10; C07F17/00; C08J5/18; B32B27/32  
EC Classification: C07F17/00, C08F10/00, C08F10/06, C08F210/16, C08J5/18, C08L23/10  
Equivalents:  [WO9967303](#)  
Cited Documents: US5747621; US5708101; EP0818458; EP0670349; EP0682042; EP0903356; EP0604917; US5585509; US5756608; EP1006149; EP0646624; EP0889089; EP0970974; EP0911349

---

### Abstract

---

A propylenic polymer according to the present invention or a composition thereof have an excellent melt flowability and contains a less amount of stickiness-causing components, and also has a low modulus and is pliable, and is capable of providing a transparent molded article, thus being useful as a substitute for a pliable vinyl chloride resin. In addition, a molded article made therefrom exhibits an excellent heat seal performance at a low temperature, and is excellent in terms of transparency and rigidity. Specifically, it has an isotactic pentad fraction (mmmm), which indicates a stereoregularity, of 30 to 80 %, a molecular weight distribution (Mw/Mn) of 3.5 or less and an intrinsic viscosity  $\eta_{\text{sp}}$  of 0.8 to 5 dl/g.

---

Data supplied from the [esp@cenet](#) database - I2